

Xtend+Climb® SuperPro



Common Dimensions

Rung Pitch (mm)	300
Rung Depth (mm)	38
Top Width (mm)	451

Product Dimensions

PRODUCT SKU	APPROX. WORKING HEIGHT (M)	LAST CLIMBING HEIGHT	RUNG COUNT	MAX. EXTENDED LENGTH (M)	CLOSED LENGTH (MM)	WIDTH (MM)	DEPTH (MM)	WEIGHT (NETT KG)
1303-071	5,0	3,5	15	4,4	943	495	118	15.7



Technical Description

The toughest, strongest and tallest Xtend+Climb telescoping ladder with a new oversize construction for the industrial user and fully certified to EN131-6. The new Xtend+Climb® Super Pro edition has thicker extruded 6061 Aerospace Grade Aluminium tube making it extremely robust with good corrosion resistance and high tensile strength typically used in heavy-duty structures including helicopter rotor skins, motor boats, military bridges and rail coaches.

- » Extends and locks rung by rung up to 4.35m
- » Heavy wall 6061 aluminium construction
- » 14% larger tubes than plus series
- » Tough nylon couplings
- » Tough black powder coated finish
- » Ergonomic easy to use design
- » Padded carry handle
- » Slip resistant feet

Standards & Classification

- » Maximum Static Vertical Load (MSVL) 150kg
- » EN131

Warranty

- » 1 Year

Shipping Dimensions

PRODUCT SKU	SHIPPING LENGTH (MM)	SHIPPING WIDTH (MM)	SHIPPING DEPTH (MM)	SHIPPING VOLUME (M ³)	SHIPPING WEIGHT (GROSS KG)	BARCODE
1303-071	925	540	140	0.0699	17.5	5060169489714